



Stage 6

Block 14, Lots 2 - 25

Block 15, Lots 2 - 21

Architectural and Landscape Guidelines

This document outlines the Architectural and Landscape Design Guidelines for Lots 2 - 25 in Block 14 and Lots 2 - 21 in Block 15, Suntree Stage 6, a comprehensively planned community in the City of Leduc.

These Guidelines will direct homebuyers, designers and builders toward appropriate building forms and details as well as lot landscaping and fencing.

This document is the mechanism whereby the Developer will exercise design control over the building design and lot landscaping and as such forms part of the Agreement for Sale as follows:

- The Purchaser agrees that the Developer prepares, implements and enforces the Design Guidelines;
- The Purchaser agrees that the Design Guidelines form a charge running with the land and shall be protected on title by the Developer by means of an encumbrance;
- The Purchaser agrees to be bound by the Design Guidelines.

No house sale is to be represented to a prospective house Purchaser as final until the Developer has given the final approval of such plans, elevations, lot siting and color scheme.

The house builder shall be fully and solely responsible for such representation.

Setting the Standard for Your New Neighbourhood

1. DESIGN GUIDELINES AND OBJECTIVES

The image of the community and general architectural theme will encourage attention to detail on homes which are well appointed and uniquely suited for the duplex lots.

The Design Guidelines are the mechanism which encourages the community to be of the highest quality, reflecting its comprehensively planned image, appropriate to the setting.

House plans will be reviewed in terms of their adherence to these Guidelines. The Developer may require certain modifications to house plans and/or specifications where it is felt that a modification is required to take advantage of unique lot characteristics or to conform to the overall objectives of the Design Guidelines.

Applicants may provide alternative details to those outlined in these Guidelines providing that it is demonstrated that conformity to the overall objectives for the quality of the area is being maintained. The acceptability of such alternatives is solely at the Developer's discretion.

2. CITY OF LEDUC STANDARDS

All developments shall comply with the City of Leduc Land Use Bylaw.

Conformity with these Guidelines does not supersede the required approval process of the City of Leduc.

3. STYLE

The natural landscaped surroundings provide the perfect setting for this collection of neo-traditional homes.

3.1 Setbacks / Separation Space

Minimum setbacks and side yards must conform to those established by the City of Leduc Land Use Bylaw.

3.2 Streetscape

Relative massing, siting and style will ensure each home compliments its neighbour and the subdivision. Entranceways will be covered at the first level to enclose and protect the space. The style, width, height and detailing of the entranceway will create a sense of welcome and arrival.

3.3 House Sizes

Houses are to have a consistency of mass and volume within the streetscape. As such, house widths and sizes must relate proportionately and logically to the lot width and neighboring houses.

Maximum square footage applies as set out in the Land Use Bylaw.

3.4 Site Planning and Grading

Site planning and grading must accommodate the natural slope of the land with variations in grade absorbed within the building mass as much as possible.

Minimum setbacks will conform with those established by the Land Use Bylaw. Siting, building mass and style may be adjusted on a lot to lot basis to enhance the streetscape.

The Builder/Purchaser must utilize the designated surveyor.

All homes shall have a maximum of 2'6" parging on all elevations.

Homes will have no more than five risers per set.

The Developer reserves the right to adjust the grading requirements between units after plans for affected homes have both been submitted. A coordinated grading review will be carried out by the Designated Surveyor to ensure that the proposed final grades of a particular house do not adversely affect the adjacent houses. The Designated Surveyor to the mutual benefit of both houses will balance the final grading requirements.

It is the responsibility of the Purchaser after the final grading is complete, to provide the Developer with a Final Lot Grading

Certificate prepared by the Designated Surveyor that has been accepted by the City of Leduc, in compliance with the approved grading plan.

Downspouts shall not be connected with the storm sewer system.

3.5 Garage/Driveway/Walkways

3.5.1 Homes must be provided with a single attached garage, constructed concurrently and located in accordance with the garage location plan. Overhead doors shall be painted to match the siding or a color that blends with the exterior. The height between the overhead door and the eave should be kept to 2'. Where design exceeds 2', special treatment may be required.

3.5.2 Front driveways may be constructed of concrete, including plain, stamped and colored concrete, colored concrete pavers and exposed or washed concrete. Where colored concrete or pavers are utilized, the color must be expressly approved.

3.5.3 The driveway is not to exceed the width of the garage, to the garage front, where the width may then flare to include a walkway to the front and/or rear yard.

3.5.4 The front walk must be a minimum 30" width of poured concrete in broom finish, exposed or washed concrete, paving stone, or approved equivalent. Individual patio blocks will not be permitted.

3.6 Repetition

Similar or approximately identical elevations must not be repeated on adjacent lots or directly across the street (XOX). Repetition on lots with high visibility must be addressed at the front and rear elevations.

Buildings will be designed to avoid mirror image of units at visible elevations. Variation in wall planes, rooflines, window groupings and finishes are some of the architectural measures that can achieve distinction between units.

Repetitive use of elevations will be monitored to ensure interesting streetscapes. Modifications to elevation treatments may be required accordingly.

4. MATERIALS

4.1 Exterior Colors

Colors will not be repeated on adjacent lots. Fascia and trim will be a single color in a strong contrast.

The use of a third accent color is required in a bright/bold selection that is not a tone of the primary colors.

4.2 Corner and High Visibility Lots

Corner Lots:

Houses on corner lots and high visibility lots require special design consideration. Flanking side elevations will have suitable front elevation treatment with principal roof planes sloping toward view. Corner elevations will require variation in wall planes, roof line between floors, appropriate wall heights, window placement and detailing. High visibility rear elevations shall require enhanced treatments.

Public Adjacency (lots backing onto MR): Lots backing onto parks and other public areas require special design consideration at the rear. These elevations will incorporate detailing consistent with the front elevation with variations in wall planes and roof lines. (Also see 3.6 Repetition)

4.3 Roofing

To provide a unifying theme throughout the subdivision, the minimum roof pitch will be 5/12. In consideration of overall massing and style, some secondary roofs may not be subject to this minimum requirement.

Roof materials will be asphalt shingles only in the color of Sandstone or Driftwood.

Roof overhangs will be proportionate to the design with suitable overhangs incorporated at cantilevers, box outs and bays.

Fascia may be 6"

All flues must be contained in a corbelled chase.

4.4 Exterior Finishes

All homes in Stage 6 shall be finished in vinyl siding.

The use of window and door surrounds and/or a combination of battens, trim boards, louvers and shutters will be featured on all homes and consistent with the neo-traditional theme.

Window surrounds will be required at the rear elevation for all lots.

Brick, stone, or tile treatment will be a requirement at the front elevation of all homes. A minimum 28 square feet will be applied with 18" returns around the side elevations for each unit. The area of the returns will be included in the minimum 28 square foot requirement.

All verandas and wood entry steps must be skirted to grade with lattice or an appropriate finishing detail on all sides

4.5 Accessory Buildings

Accessory buildings must be consistent in style, finish and color with the house and meet the City of Leduc's requirements for site coverage. Accessory buildings are a maximum of 10 feet by 10 feet in dimension.

5. LANDSCAPING & FENCING

5.1 Sod & Planting

All front yards and side yards to the side yard fence tie back must be completely sodded over a minimum of 6" of topsoil. The Purchaser is to prepare all surfaces to final grade. Sod is to be placed to the curb.

On all corner lots, sod shall be placed over the entire sideyard at the flanking street, to include the boulevard, from the front of the lot to the rear property line.

All lots require one front yard tree with minimum 7' height for coniferous trees or 2" caliper for deciduous trees (measured 1' above root ball).

5.2 Timing

All landscaping must be completed, in accordance with the requirements, within six months of completion of the house, subject to seasonal limitations.

5.3 Fencing

All fencing must be installed so that the bottom of the fence is 2" above final design grade.

The following lots will have the rear yard fenced with wood screen fencing: Block 15, Lot 2-21, Block 14, Lots 11-13 and the side yard of Block 15, Lot 21 adjacent to lot 22 PUL and the side yard of Block 14, Lot 25 adjacent to Sheridan Way.

The following lots will have the rear yard fenced with black vinyl coated chain link fencing with gates: Block 14 Lots 2-10 and 14-25.

All other purchaser installed fencing must be consistent in terms of design, color and detail with the wood screen fence specification attached as Schedule A.

6. OTHER IMPORTANT GUIDELINES

6.1 Appearance During Construction

Each purchaser must inspect the condition of the local improvements installed by the Developer including but not limited to curbs, gutters, sidewalks, street lamps, fencing, parks and landscaping etc. in, on, or around his or her lot prior to commencement of construction in order to determine if any of these local improvements are damaged. Written notice of any damages must be submitted to the Developer prior to commencement of construction. Otherwise costs for repairing damage shall become the sole responsibility of the Purchaser.

Under no circumstances may construction access be taken across designated park spaces.

The Purchaser is required to keep his or her lot clean and orderly during construction. The Purchaser may not deposit any material including building, landscaping, fill or other

materials deemed to be garbage or excess on the lots of others. There will be no burning of garbage. Purchasers not complying will be charged for clean-up carried out by the Developer.

7. APPROVAL PROCESS

7.1 Covenant

No construction will be commenced until the approval of the Developer or its Designated Consultant is obtained.

7.2 Initial Submission

The Purchaser shall submit the following information to the Developer or its Designated Design Consultant ten days in advance of desired start date:

- one set construction drawings of the house (3/16" or 1/8" = 1'0");
- two copies of site plan prepared by the Designated Surveyor, identifying the building location, grades and elevations (1:300);
- a completed application form for House Plan Approval (indicating materials, colors, finishes and other specific information as requested on the form);
- color and/or material samples as may be requested.

The Developer or its Designated Design Consultant shall review the plan and recommend approval or rejection of the application based on adherence of the plans to the Guidelines. Modifications may be required as conditions of approval. The Developer will make the final decision as regards approval or rejection of the application. A copy of the application form and approved exterior elevation marked with any changes shall then be made available to the Purchaser. The original application form and construction drawings will be kept on file for future reference.

Any changes by the Purchaser from approved plans must be submitted to the Developer or its Designated Design Consultant for approval in writing.

Incomplete applications will be returned to the Applicant.

7.3 Interim Building Review

The Designated Design Consultant may carry out an on-site review of the homes during construction. Periodic checks may be made to ensure conformance to approved plans and Guidelines. Modifications may be requested related to actual site conditions.

7.4 Final Building Approval

Upon being advised by the Purchaser of the completion of the home, the Developer's Design Consultant shall carry out a site review to confirm conformance to the Guidelines and approval previously granted. The enforcement, administration and interpretation of these Guidelines shall be at the sole discretion of the Developer, or its designated consultant. The decision of the Developer, or its designated consultant, in interpreting these Guidelines shall be final and binding upon the Purchaser.


7.5 Refund of Security Deposit

Following the final Building Approval, the completion of any deficiencies, the acceptance of the lot grading certificate, the completion of the required lot landscaping and confirmation that no other funds are due to the Developer, the security deposit will be refunded by the Developer.


Please note: The submission deadline for home inspections with the Developer's current design consultant is September 30. Any submissions after that date are carried over until the following spring.

The information contained in the Design Guidelines document is provided as a guide to be used by the Lot Purchaser, and the Developer may revise these Guidelines at its discretion. The Developer and its designated consultants make


no warranties or representations as to the accuracy, suitability or completeness of any information provided on individual house plans. The Purchaser shall be fully and solely responsible for all designs, which follow these Guidelines, and for the conformance of such design to the appropriate building codes.



1 WOOD SCREEN FENCE STEP-DOWN DETAIL
L14 SCALE: 1:50



2 1800mm HT. WOOD SCREEN FENCE
L14 SCALE: 1:20



WOOD FENCING NOTES:

1. ALL TIMBER POSTS TO BE PRESSURE TREATED SPRUCE PAINTED WITH TWO COATS STAIN.
2. ALL LUMBER SHALL BE CLEAN, #1, CONSTRUCTION GRADE SPRUCE MEMBERS, FINISHED AS PER THE DETAILS UNLESS OTHERWISE SPECIFIED.
3. ALL LUMBER SHALL BE STRAIGHT, SOUND AND FREE OF SPLINTS, WARPS, CRACKS, LARGE KNOTS AND OTHER DEFECTS.
4. ALL COLORS AND TYPE OF STAIN ARE AS PER THE DETAILS AND TO BE APPLIED AS PER MANUFACTURER'S SPECIFICATION AND ARE TO BE SUBMITTED TO THE OWNER FOR APPROVAL PRIOR TO PROCEEDING.
5. ALL WOOD TO BE PRE-STAINED WITH "MONTREX GRET" SOLID HIDE STAIN BY CLOVERDALE PAINT BOTH SIDES PRIOR TO INSTALLATION.
6. ALL DIMENSIONS ARE IN MILLIMETERS (mm) UNLESS OTHERWISE NOTED.
7. ENSURE THAT FRONT OF POST IS 1.5 METERS FROM GAS LINE.
8. ALL WOOD SCREEN FENCES TO BE PLACED 150mm. INSIDE PRIVATE PROPERTY.
9. ALL HARDWARE TO BE GALVANIZED.
10. PRESSURE TREATED POSTS TO BE TREATED WITH A SOLUTION OF PENTACHLOROPHENOL AND PETROLEUM TO CSA-080.
11. NAILS TO BE 89mm ARDOX COATED FOR STRINGERS AND POSTS AND 50mm ARDOX COATED FOR BOARDS.
12. CONTRACTOR TO CALL ALBERTA FIRST CALL AT 1-800-242-3447 TO HAVE EXISTING UTILITIES LOCATED PRIOR TO START OF ANY CONSTRUCTION.
13. THIS DRAWING TO BE READ IN CONJUNCTION WITH THE WRITTEN SPECIFICATIONS, DRAWINGS AND DETAILS FOR THE PROJECT.